





ENDOSKOPAI PRAMONINIAI

Eil. Nr.	Vaizdas	Modelis	Aprašymas
1.		SZ701F	Camera probe lens: 20mm x 7.0mm, 360° rotation. Cable: 1m/ 2m/ 3m. Monitor : 3.5''. Articulations: 4-way, ≥120°. Pixels: 410000. View angle: 80°. DOF: 10mm--∞. SD card: 4GB. 6 times zoom in and zoom out. Resolution: 800x640 .Color: blue/white/ Red .
2.		SZ702F	
3.		SZ703F	
4.		SZ501T	Camera probe lens: 20mm x 5.3mm, 360° rotation. Cable: 1m/ 2m/ 3m. Monitor : 3.5''. Tip articulations: 2-way, ≥120°. Pixels: 410000. View angle: 80°. DOF: 10mm-- 150mm / 25mm -- infinity . SD card: 4GB. 6 times zoom function. Resolution: 640x480 .Color: blue/white/ Red .
5.		SZ502T	
6.		SZ503T	
7.		SZJ601F	Camera probe lens: 18mm x 6.0mm, Cable: 1.2m. Monitor : 3.5''. Articulations: 4-way, ≥150°. Pixels: 400000. View angle: 75°. DOF: 10mm--∞. SD card: 4GB. 3 times zoom. Resolution: 640x480 . Room function : 5 times .
8.		TJ601T	Camera probe lens: 18mm x 5.5mm, 360° rotation. Cable: 1m/ 2m/ 3m. Monitor : 3.5''. Articulations: 2-way, ≥120°. Pixels: 380000. View angle: 70°. DOF: 10mm--∞. SD card: 4GB. Resolution : 640 x 480 . Room function : 5 times .
9.		TJ602T	
10.		TJ603T	
11.		SZ401T	Camera probe lens: 15mm x 4.1mm, 360° rotation. Cable: 1m/ 2m/ 3m. Monitor : 3.5''. Tip articulations: 2-way, ≥120°. Pixels: 300000. View angle: 75°. DOF: 8mm--150mm. SD card: 4GB. Resolution : 640 x 480 . Room function : 3 times
12.		SZ402T	
13.		SZ403T	
14.		SZ601F	Camera probe lens: 20mmx6.0mm, Cable: 1m/ 2m/ 3m. Monitor: 3.5''. Pixels: 410000. View angle: 70°--90°. DOF: 10mm--150mm/ 20mm -- infinity. SD card: 4GB. Resolution : 800 x 640 . Zoom function : 5 times . Tip articulation : 4-way .
15.		SZ602F	
16.		SZ603F	
17.		SZR601T	Camera probe lens: 20mm x 5.5mm, 360° rotation. Cable: 1m/ 2m/ 3m. Monitor : 3.5''. Articulations: 2-way, ≥120°. Pixels: 380000. View angle: 80°. DOF: 15mm--∞. SD card: 8GB. Resolution : 640 x 480 . 3 times zoon function
18.		SZR602T	
19.		SZR603T	
20.		SZR601F	Camera probe lens: 20mm x 5.8mm, 360° rotation. Cable: 1m/ 2m/ 3m. Monitor : 3.5''. Tip articulations: 4-way, ≥120°. Pixels: 450000. View angle: 80°. DOF: 10mm--200mm / 25mm -- infinity. SD card: 8GB. Resolution : 800 x 640 . 3 times room function
21.		SZR602F	
22.		SZR603F	

23.		SZR401T	
24.		SZR402T	Camera probe lens: 15mm x 3.9mm, 360° rotation. Cable: 1m/ 2m. Monitor : 3.5" TFT LCD. Tip articulations: 2-way, ≥120°. Pixels: 310000. View angle: 80°. DOF: 8mm--150mm. SD card: 4GB. Resolution : 640 x 480 . Room function : 5 times
25.		SZR403T	
26.		SZR403T	Camera probe lens: 10mm x 2.6mm, Cable: 1m. Monitor : 3.5". Articulations: 2-way, ≥100°. Pixels: 180000. View angle: 70°. DOF: 8mm--150mm. SD card : 4GB. Resolution : 640 x 480 . It is specially fit for inspection in narrow engine or space !
27.		SHPVC601F	Camera probe lens: 20mm x 6.0mm/8.0mm. Cable: 1m, 2m, 3m. Monitor : 5.1". Articulations: 4-way, ≥120°. Pixels: 440000. LED and fiber optic light. View angle: 70--80°. DOF: 10mm--150mm / 20mm -- infinity. SD card: 4GB. Resolution : 800 x 640 . (Fiber optic / infrared light is optional)
28.		SHPVC602F	
29.		SHPVC603F	
30.		SHPVC806F	
31.		SHHVC601F	Camera probe lens: 20mm x 6.0mm/8.0mm. Cable: 1m, 2m, 3m. Monitor : 3.5". Articulations: 4-way, ≥120°. Pixels: 380000. View angle: 70--80°. DOF: 20mm--∞. SD card: 4GB. Resolution : 640 x 480 . (Fiber optic / infrared light is optional)
32.		SHHVC602F	
33.		SHHVC603F	
34.		SHMVC601F	Camera probe lens: 18mm x 6.0mm/8.0mm. Cable: 1m, 2m, 3m. Monitor : 5.1". Articulations: 360 degrees rotation by joystick control, ≥120°. Pixels: 450000. View angle: 70--80°. DOF: 10mm--∞. SD card: 4GB. Resolution : 800 x 600 . (Fiber optic/ infrared light is optional)
35.		SHMVC602F	
36.		SHMVC603F	
37.		YK601F	Camera probe lens: 20mm x 6.0mm/8.0mm, Cable: 1m/ 2m/ 3m/ 6m. Monitor : 3.5". Tip articulations: 4-way, ≥120°. Pixels: 410000. View angle: 70°. DOF: 10mm--150mm / 20mm -- infinity. SD card: 8GB. Resolution : 480 x 640 . Waterproof : IP66 (Fiber optic/ infrared light is optional)
38.		YK602F	
39.		YK603F	
40.		YK806F	
41.		YKR601F	Camera probe lens: 20mm x 6.0mm/8.0mm, Cable: 1m/ 2m/ 3m/ 6m. Monitor : 5.0". Tip articulations: 4-way, ≥120°. Pixels: 440000. View angle: 80°. DOF: 10mm--200mm / 20mm -- infinity. SD card: 8GB. Resolution : 800 x 600 . Waterproof : IP67 .(Fiber optic/ infrared light is optional)
42.		YKR602F	
43.		YKR603F	
44.		YKR806F	
45.		YKJ601F	Camera probe lens: 20mm x 6.0mm. Cable: 1m, 2m, 3m. Monitor : 5.1". Articulations: 360 degrees rotation by joystick control, ≥120°. Pixels: 450000. View angle: 70 -- 80°. DOF: 10mm--∞. SD card: 4GB. Resolution : 800 x 600 . Waterproof : IP67 . (Fiber optic/ infrared light is optional)
46.		YKJ602F	
47.		YKJ603F	

48.		SZxxD	Camera diameter : 3.9mm/5.5mm/8.5mm/10mm, Cable length : 1m -- 10m. Monitor: 3.5". Pixels: 300000. View angle: 60°--70°. DOF: 10mm--150mm. SD card: 4GB. Resolution : 640 x 480 . Zoom function : 5 times. Waterproof standard : IP66 .
49.		SZRxxD	Camera diameter : 3.9mm/5.5mm/8.0mm, Cable length : 1m -- 20m. Monitor: 3.5". Pixels: 400000. View angle: 70°--80°. DOF: 5mm--200mm. SD card: 8GB. Resolution : 640 x 480 . Waterproof standard : IP67 .
50.		YKxxD	Wireless, Camera diameter : 3.9mm/5.5mm/8.0mm, Cable length : 1m -- 15m. Monitor: 3.5". Pixels: 300000. View angle: 70°--80°. DOF: 10mm--200mm. SD card: 8GB. Resolution : 640 x 480 . Waterproof standard : IP66 .
51.		YKZxxD	Camera diameter : 3.9mm/5.5mm/8.0mm, Cable length : 1m -- 10m. Monitor: 3.5". Pixels: 300000. View angle: 70°--80°. DOF: 8mm--150mm. SD card: 8GB. Resolution : 640 x 480 . Waterproof standard : IP66 .
52.		YKHxxD	Camera diameter : 3.9mm/5.5mm/8.0mm, Cable length : 1m -- 10m. Monitor: 2.4". Pixels: 300000. View angle: 70°--80°. DOF: 8mm--150mm. SD card: 8GB. Resolution : 640 x 480 . Waterproof standard : IP66 .
53.		YK22xx	Resolution : 420 TV Lines, camera : 22mmx135mm, Camera material : Enhances ABS, Vew angle : 60°, 12 LED lights, Waterproof standard : IP68, Cable length : 20m / 30m / 40m , LCD resolution : 800x640, LCD size : 7 inches, Wheel diameter : 33cm .
54.		YK60xx	Resolution : 720 TV Lines, camera : 60mmx120mm, Camera material : Enhances ABS, Vew angle : 80°, 24 LED lights, Waterproof standard : IP68, Cable length : 60m / 90m / 120m , LCD resolution : 800x640, LCD size : 7 inches, Wheel diameter : 60cm .
55.		YKZ6xxT	Probe lens: 20mm x 5.5mm,360° rotation. Cable: 1m/ 2m/ 3m. Monitor : 3.5". Articulations: 2-way, ≥120°. Pixels: 300000.View angle: 70°. DOF: 10mm--∞. SD card: 4GB. Resolution : 640 x 480 .
56.		YK3601	Auto pan 360° / tilt 180° , SONY CCD, 480TVL 7" TFT Monitor, Resolution : 720x576 Cree brand LED, 18 LED lights, Cable length : 120m (max), Battery : DC12V / 14.8V 8500mah,

57.		YK3602	Auto pan 360° / tilt 220° , SONY CCD, 600TVL 5.7'' TFT Monitor, Resolution : 800x640 Cree brand LED, 20 LED lights, Cable length : 120m (max), Battery : DC12V / 14.8V 4000mah, Camera diameter : 51mmx120mm .
-----	---	---------------	--