




ATSTUMO MATUOKLIAI AUTOMOBILINIAI NU-METRICS

| Eil. Nr. | Aprašymas |
|----------|--|
| 1. |  <p>NITESTAR NS-50 Accuracy: $\pm 1'$. Resolution: 1'. Speed: display vehicle speed 0-199 (MPH, Kmh, F/S). Count: Bi-directional Up/Down. Calibration: automatic, manual, four vehicle memory. Automatic distance conversion: feet, miles, kilometers. Count hold: stops distance count. Display hold: freeze display count without loss of accumulating distance. Automatic error correction: compensates for sensor error due to vehicle's dynamic motion. Operating temperature: 0°C to 70°C. Power: 9 to 16 VDC, negative ground 90 ma @ 12 VDC (max). Case: high heat resistive ABS. Dimensions: 7.5" x 2.25" x 0.88". Weight: 7 oz.</p> |
| 2. |  <p>NITESTAR NS-60 Communications: RS-232 in/out, selectable baud rate (300-9,600). Accuracy: $\pm 1'$. Resolution: 1'. Speed: display vehicle speed 0-199 (MPH, Kmh, F/S). Count: Bi-directional Up/Down. Calibration: automatic, manual, four vehicle memory. Automatic distance conversion: feet, miles, kilometers. Count hold: stops distance count. Display hold: freeze display count without loss of accumulating distance. Automatic error correction: compensates for sensor error due to vehicle's dynamic motion. Operating temperature: 0°C to 70°C. Power: 9 to 16 VDC, negative ground 90 ma @ 12 VDC (max). Case: high heat resistive ABS. Dimensions: 7.5" x 2.25" x 0.88". Weight: 7 oz.</p> |
| 3. |  <p>NITESTAR DMI Proximity Sensor</p> |

4.



NITESTAR DMI SS-10 Universal Speed Sensor

5.



NITESTAR DMI Target Kit

6.



NITESTAR DMI Cable Kit

7.



NITESTAR DMI Vehicle Installation Kit

8.



NITESTAR DMI TCI200 OBD-II Adapter

Allows the DMI to be used in virtually any vehicle with an OBDII port, without the need to hook up any additional wiring to the vehicle. Note: On some vehicles - specifically trucks, the

OBDII adapter will not report the proper speed to the DMI display, resulting in lower than actual distances measured. For the vehicles on which this problem has been observed, the distance recorded will be less than 10% of actual.

9.



NITESTAR DMI RS-232 Download Cable