

FLIR THERMOVISION KAMEROS

Eil. Nr.	Modelis	IR detektoriaus raiška (vaizdo taškai)	Šiluminis jautrumas (°C)	Maksimali matuojama temperatūra (°C)	Kadru dažnis (Hz)
1.	 <u>FLIR E4</u>	80 × 60	<0.15	250	9
2.	 <u>FLIR E4-NIST</u>	80 × 60	<0.15	250	9
3.	 <u>RE5</u> <u>FLI</u>	120 × 90	<0.10	250	9
4.	 <u>FLIR E5-NIST</u>	120 × 90	<0.10	250	9
5.	 <u>FLIR i7</u>	140 x 140	<0.10	250	9
6.	 <u>FLIR i7-NIST</u>	140 x 140	<0.10	250	9

7.	 <u>FLIR E6</u>	160 × 120	<0.06	250	9
8.	 <u>FLIR E6 NIST</u>	160 × 120	<0.06	250	9
9.	 <u>FLIR E30</u>	160 × 120	<0.10	350	60
10.	 <u>FLIR E40</u>	160 x 120	<0.07	650	60
11.	 <u>FLIR E40 BX</u>	160 x 120	<0,045	120	60
12.	 <u>FLIR E40-NIST</u>	160 x 120	<0.07	650	60

13.	 <u>FLIR R E40 BX-NIST</u>	160 x 120	<0.045	120	60
14.	 <u>FLIR i40</u>	120 x 120	<0.1	350	?
15.	 <u>FLIR E8</u>	320 × 240	<0.06	250	9
16.	 <u>FLIR E8 NIST</u>	320 × 240	<0.06	250	9
17.	 <u>FLIR E50</u>	240 x 180	<0.05	650	60
18.	 <u>FLIR E50-NIST</u>	240 x 180	<0.05	650	60
19.	 <u>FLIR E50BX</u>	240 x 180	<0,045	120	60

20.	 <u>FLIR E50BX-NIST</u>	240 x 180	<0,045	120	60
21.	 <u>FLIR E60</u>	320 x 240	<0.05	650	60
22.	 <u>FLIR E60BX</u>	320 x 240	<0.045	120	60
23.	 <u>FLIR E60-NIST</u>	320 x 240	<0.045	120	60
24.	 <u>FLIR E60BX-NIST</u>	320 x 240	<0.045	120	60
25.	 <u>FLIR T420</u>	320 x 240	<0.045	650	60