

FLUKE THERMOVISION KAMEROS

Eil. Nr.	Modelis	IR detektoriaus raiška (vaizdo taškai)	Šiluminis jautrumas (°C)	Maksimali matuojama temperatūra (°C)	Kadrų dažnis (Hz)
1.	 <p style="text-align: center;"><u>FLUKE TIS</u></p>	120 x 120	<0,1	100	9
2.	 <p style="text-align: center;"><u>FLUKE T19</u></p>	160 x 120	<0,2	250	9
3.	 <p style="text-align: center;"><u>FLUKE Ti100</u></p>	160 x 120	<0,1	250	9
4.	 <p style="text-align: center;"><u>FLUKE Ti105</u></p>	160 x 120	<0,1	250	30
5.	 <p style="text-align: center;"><u>FLUKE TiR 105</u></p>	160 x 120	<0,1	250	9
6.	 <p style="text-align: center;"><u>FLUKE Ti110</u></p>	160 x 120	<0,1	250	30

7.	 <u>FLUKE TiR 110</u>	160 x 120	<0,1	250	9
8.	 <u>FLUKE TI 10</u>	160 x 120	<0,2	250	9
9.	 <u>FLUKE TI 25</u>	160 x 120	<0,1	350	9
10.	 <u>FLUKE TiR 125</u>	160 x 120	<0,1	350	9
11.	 <u>FLUKE Ti 125</u>	160 x 120	<0,1	350	30
12.	 <u>FLUKE Ti 200</u>	200 x 150	<0,075	650	60
13.	 <u>FLUKE Ti 27</u>	240 x 180	<0,05	600	60

14.		<u>FLUKE TIR 27</u>	240 x 180	<0,045	150	60
15.		<u>FLUKE Ti 300</u>	240 x 180	<0,05	650	60
16.		<u>FLUKE TI 29</u>	280 x 210	<0,05	600	60
17.		<u>FLUKE TIR 29</u>	280 x 210	<0,045	150	60
18.		<u>FLUKE TI 32</u>	320 x 240	<0,05	600	60
19.		<u>FLUKE TIR 32</u>	320 x 240	<0,04	150	60
20.		<u>FLUKE Ti 400</u>	320 x 240	<0,05	1200	60