



# KOMERCINIS PASIŪLYMAS

## Šviesos matavimo prietaisai LM-120, LT300

Eil. Nr.	Aprašymas
1.	 <p><b>Light meter LM-120. Kilmės šalis JAV.</b></p> <ul style="list-style-type: none"><li>•Silicon photodiode sensor and filter and cap</li><li>•Data Hold to freeze reading on the digital display</li><li>•MIN / MAX ability to show high and low readings</li><li>•Autoranging plus Manual Range</li><li>•Zero function to null display before a reading</li></ul> <p>Range 20, 200, 2000, 20000, 200000 Lux Accuracy ± 3%. Resolution 0.01 lux Display 3¾ digit liquid crystal display (LCD) with a maximum reading of 1999 Sampling Rate 2.5 times per second for digital display Overrange (OL) or (-OL) is displayed Temperature / Humidity Operating: -10°C to 50°C (14°F to 122°F), 0 to 80%RH Storage: -10°C to 50°C (14°F to 122°F), 0 to 70%RH Altitude 2000m, indoor operation Power Supply 9V NEDA 1604, IEC 6F22, JIS 006P battery. Low battery indication. Battery Life 200 hours. Auto Power Off approx 6 min Dimension (Base) 130 x 63 x 38 mm (5.1 x 2.5 x 1.5") Dimension (Sensor) 80 x 55 x 29 mm (3.2 x 2.2 x 1.1") Weight 220 g (.48 lb.) include battery Agency Approvals and certifications: EN61326-1 This product complies with requirements of the following European Community Directives: 89/336/EEC (Electromagnetic Compatibility) and 73/23/EEC (Low Voltage) as amended by 93/68/EEC (CE Marking).</p>
2.	 <p><b>Apšviestumo matavimo prietaisas LS-200. Kilmės šalis Lenkija.</b> Matavimo ribos: 0.1Lx – 199.9Lx, 1Lx – 1999Lx, 10Lx – 19.99kLx. Tikslumas 3%.</p>

3.



**Light meter LT300. Kilmés šalis JAV.**

- **Relative mode indicates change in light levels**
- **Peak mode capture highest reading**
- **Remote light sensor on 12" (30.5cm) coiled cable — expandable to 24" (61cm)**
- **Utilizes precision photo diode and color correction filter**
- **Cosine and color corrected measurements**
- **Measures up to 400,000Lux with 0.01 rmax resolution and basic accuracy of  $\pm(5\% \text{ rdg} + 0.5\% \text{ FS})$**
- **MIN/MAX feature stores maximum and minimum readings**
- **Data Hold freezes reading in the display**
- **Large LCD display with analog bargraph**
- **Backlight for readings in low light levels**
- **Dimensions: 5.9 x 2.95 x 1.57" (150 x 75 x 40mm); Weight: 7oz (200g)**
- **Complete with 9V battery, light sensor with protective cover, protective holster, and soft case**