

EcoLine Series Ceiling Configuration



Technical data	Eco Line
Reflector System	4
Illumination Intensity	100000 Lux
LED Service Life	40000 Hours
Colour Temperature	5200 K
Colour Rendering Index	90 Ra
Temperature Increase in Surgoen's head area	< 2° C
Index Light Spot	220 - 280 mm
Brightness Adjustment	Nearly 0% - 100% From Panel.
Power	230 VAC / 50 / 60 Hz

Classification

Model Name	Eco Line.
Power	230 VAC / 50 / 60 Hz
Available upon special request	110V/50~60Hz
Note : power supply is defaulted as standard configuration. please make comment on special request for 110V and mention clearly in Purchase Order. Shipment date for special request might be later then standard please contact our salesperson to confirm.	
Certification	CE Mark, ISO 9001 and ISO 13485
Standard Followed	ISO 9001-2008, EN ISO 13485:2003 / AC 2007 BS EN 980-2008, BS EN 45014-98, BS EN ISO 14971:2009, BS EN 45014 -98, EN 62366:2008, IEC 60601-1-2-2007, IEC 60601-1-4

Packing / Packaging List

- ▶ Eco Line Dome
- ▶ Sterilized Handle
- ▶ Control Panel
- ▶ Ceiling Arms