

Colour Series Ceiling Configuration



Technical data	Vari Col
Reflector System	4
Illumination Intensity	140000 Lux
LED Service Life	50000 Hours
Colour Temperature	3800 K - 6800 K variable.
Colour Rendering Index	Variable
Temperature Increase in Surgoen's head area	< 2° C
Index Light Spot	200 - 250 mm
Brightness Adjustment	Nearly 20% - 100% From Panel or Remote Control

Classification

Model Name	Vari Col
Power	230 VAC / 50 / 60 Hz
Available upon special request	110V/50~60Hz
Note : power supply is defaulted as standard configuration. please make comment on special request for 110V and mention clearly in Purchase Order. Shipment date for special request might be later then standard please contact our salesperson to confirm.	
Certification	CE Mark, ISO 9001 and ISO 13485
Standard Followed	ISO 9001-2008, EN ISO 13485:2003 / AC 2007 BS EN 980-2008, BS EN 45014-98, BS EN ISO 14971:2009, BS EN 45014 -98, EN 62366:2008, IEC 60601-1-2-2007, IEC 60601-1-4

Packing / Packaging List

- ▶ Vari Col Dome
- ▶ Sterilized Handle
- ▶ Control Panel
- ▶ Remote Control
- ▶ Ceiling Arms