

Colour Series Mobile Configuration



Technical data	Vari Col - M
Reflector System	4
Illumination Intensity	140000 Lux
LED Service Life	50000 Hours.
Colour Temperature	3800 K - 6800 K Variable
Colour Rendering Index	Variable
Temperature increase in Surgeon's head area	< 2 ° C
Index Light Spot	200 - 250 mm
Brightness Adjustment	Nearly 20% - 100% From Panel or Remote Control

Classification

Model Name	Vari Col - M
Power	230 VAC / 50 / 60 Hz
Available upon special request	110V/50~60Hz
Note : power supply is defaulted as standard configuration. please make comment on special request for 110V and mention clearly in Purchase Order. Shipment date for special request might be later then standard please contact our salesperson to confirm.	
Certification	CE Mark, ISO 9001 and ISO 13485
Standard Followed	ISO 9001-2008, EN ISO 13485:2003 / AC 2007 BS EN 980-2008, BS EN 45014-98, BS EN ISO 14971:2009, BS EN 45014 -98, EN 62366:2008, IEC 60601-1-2-2007, IEC 60601-1-4

Packing / Packaging List

- ▶ Vari Col - M Dome
- ▶ Sterilized Handle
- ▶ Control Panel
- ▶ Remote Control
- ▶ Mobile Arms